

Anti Fouling Remover

Technical Data Sheet

Publication date: March 9th 2021

Applications:

Anti Fouling Remover is an absolutely safe, pasty, pH-neutral stripper for the easy removal of old antifouling layers (even 2-component systems). It contains no harmful acids, lyes, NMP, Methylene Chloride, DMSO, paraffin or other preservatives. Leave the product to penetrate for longer to remove multiple layers in one go. The Anti Fouling Remover does not dry out and can be left for 24 hours without damaging the surface. It can even be used in temperatures as low as 0 °C.

Instructions for use:

1. Anti Fouling Remover is a paste and should be applied with a brush or paint roller.
2. Allow the product to act for 20 - 120 minutes for common antifouling layers. In the case of 2-component antifouling layers, apply the product at the end of the day so it can act overnight.
3. The old antifouling layer can then safely and easily be removed using a paint scraper or putty knife. This will also allow removing multiple layers at once.
4. Anti Fouling Remover can be applied to large areas in one go, since the product does not dry out quickly. This means you can work more efficiently and easily. This will also allow removing multiple layers at once.

Product usage:

Light to moderate soiling	Approx 10 m2 per litre
Moderate to heavy soiling	Approx 8 m2 per litre
Heavy soiling	Approx 5 m2 per litre

The above usage is indicative and should be determined by first applying to a small test area. Depends on the layer thickness and quality of the layer to be removed.

Considerations during application:

Always place a reference test on the to be treated surfaces in order to determine both adhesion and the technical and aesthetic result.

Specifications:

Appearance:	Liquid
Color:	Blue/Green
Scent:	Characteristic
pH:	Neutral
Density:	1,100 g/cm ³
Degradability:	Biologically optimal

Hazard symbols and H & P statements (CLP):

Anti Fouling Remover is not categorised in accordance with Regulation (EC) no. 1272/2008 (CLP). However, it is advisable to wear PPE at all times. Please consult the MSDS sheet for this.

Packaging and industrial waste:

Treat as industrial waste in accordance with the applicable regulations. Collect process water in accordance with the applicable local regulations.

This information is based on laboratory tests and practical experience.

For application and use, please adhere strictly to the descriptions in the technical product information sheets and MSDS sheets. We do not accept any liability for any advice provided by us. The application, use and handling of the products are the sole responsibility of the user. All our documents and texts have been prepared to the best of our knowledge, language and translation errors are expressly excluded and can never lead to any liability.

Anti Fouling Remover is part of the Impressed Pro[®] Marine product range, developed to clean and preserve all types of all common surfaces and materials on and around boats and/or ships. For specific questions and applications, as well as for the up-to-date TDS and MSDS sheets, please visit our website www.impressedpro.com or contact your distributor and / or technical advisor.

Produced and developed by:

Cleaning Care Products International B.V.
Noord 49 L-M, 2931 SJ Krimpen aan de Lek - The Netherlands
www.ccp.nl - info@ccpi.nl

Exclusive distributor:

Alpha Marine Pro
Willem Alexanderlaan 34, 4532 DB Terneuzen - The Netherlands
www.alphamarinepro.com - info@AlphaMarinePro.com